AIR TUROUDISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 . CH-1844 Villeneuve . + +41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Harness inspection certificate - NfL

Inspection certificate number:

PH 410.2023

Impact pad number:

MISC 254.2023

Manufacturer data

Manufacturer name: Representative:

Woody Valley srl Simone Caldana

Street:

Via Linz 23

Post code / place: Country: 38121 Trento Italy

Sample data:

Harness

Impact pad

Name:

MK1

Name Impact pad: (1)

MK FOAM PROTECTION

Type:

ABS M Impact pad integrated: (1)
Impact pad type:

No Foam

Size: Weight of Sample [kg]:

7.24

Weight of Sample [kg]: (1)

Date of reception:

0.96 107 0115 002P

Serial number: Clip-in weight [kg]:

120

Serial number:(1)

107 0110 0021

Integrated container for rescue system:

Yes

10000 max

5000 min

Volume container [cm³]:

Date of reception:

25.05.2023

114 01150 0005

07.09.2022

Test report summary

Structual test

Impact pad test

Result Place Date POSITIVE Villeneuve 25.05.2023 POSITIVE Villeneuve 07.09.2022

Issue data

Place of declaration:

Date of issue:

Managing Director:

Villeneuve 12.07.2023

Andrea Wigger

Signature:

This signature approves the validity of the test reports if available; no. 94.21 (test id 02, 03, 13, 09, 04, 14, 07) and no. 94.22 (test id: P, PR)

Air Turquoise SA, having thoroughly assessed the sample mentioned above, declares it was found conform with all requirements defined by the following norms:

Airworthiness Requirements NfL 2-565-20 - EN12491:2015 5.3.2

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above.

This inspection certificate contains the following test and is complet with the test, if available, report: 94.21 and 94.22

⁽¹⁾ If Impact pad is NOT integrated in the harness, it will have independently Inspection number, and serial number. Definition of integrated impact pad is impact pad which can not be dismounted from the harness, e.g. airbag. (2) If harness has an integrated inner container for emergency parachute, extra deployment tests are done for different type of emergency parachute.